


YB-P18HP

Global Flex Crimping Machine

P18HP hose crimping machine has been designed to crimp up to 1" diameter 4-spiral hoses. It is hand pump operated hydraulic crimping machine for repair workshops and field use.

Easy to use, light and compact in size





GLOBAL FLEX

TECHNICAL DATA

Max crimping dia (mm)	10 - 54	
Max crimping dia (inches)	0.39 - 2.13	
Max crimping force (kN)	955	
Max crimping force (tonnage)	95	
Cycle time 10mm (s)	-	
Hose size ID (inches)	1*4sp	
Die set series	P18	
Max opening (mm)	+20	
Max opening without dies (mm)	68	
Master die D/L (inches)	1.89/2.52	
Motor power (kW/HP)	-	
Oil tank volume (L)	-	

P18 DIES

DieSetNo	Crimping Range	ID (mm)	L (mm)
P18/06*	6.0 - 8.0	6	55
P18/08*	8.0 - 10.0	8	55
P18/10*	10.0 - 12.0	10	55
P18/12*	12.0 - 14.0	12	55
P18/14	14.0 - 16.0	14	55
P18/16	16.0 - 19.0	16	55
P18/19	19.0 - 23.0	19	55
P18/23	23.0 - 27.0	23	55
P18/27	27.0 - 31.0	27	65
P18/31	31.0 - 36.0	31	65
P18/36	36.0 - 41.0	36	65
P18/41	41.0 - 47.0	41	65

*Non standard dies (not included with the Swaging Machine)



Hydraulic Hose & Fittings

Looking for hydraulic hose and fittings to go with your new swaging machine? We stock large quantities of hydraulic hose and fittings for use across every industry including; 1 wire, 2 wire, 4 wire and 6 wire hose, and fittings available in mild or stainless steel.

Looking to start a mobile hose replacement business?

We have a recommended starting stock list for any new van, speak to our sales team to discuss your specific needs.

30+ Years in the Hydraulic Industry





