


YB-P20CS

Global Flex Crimping Machine

P20CS hose crimping machine has been designed to crimp up to 11/2" diameter4-spiral hoses. For car-service use, it is fast and easy to use. CS machines are battery powered with 12V or 24V







TECHNICAL DATA

Max crimping dia (mm)	10 - 21	
Max crimping dia (inches)	0.39 - 2.40	
Max crimping force (kN)	1370	
Max crimping force (tonnage)	137	
Cycle time 10mm (s)	7.2	
Hose size ID (inches)	1.5	
Die set series	P20	
Max opening (mm)	+25	
Max opening without dies (mm)	109	
Master die D/L (inches)	3.31/3.15	
Motor power (kW/HP)	1.6/2.25	
Oil tank volume (L)	4	

P20 DIES

DieSetNo	Crimping Range	ID (mm)	L (mm)
P20/06*	6.0 - 8.0	6	55
P20/08*	8.0 - 10.0	8	55
P20/10*	10.0 - 12.0	10	55
P20/12*	12.0 - 14.0	12	55
P20/14*	14.0 - 16.0	14	55
P20/16	16.0 - 19.0	16	55
P20/19	19.0 - 23.0	19	55
P20/23	23.0 - 27.0	23	55
P20/27	27.0 - 31.0	27	70
P20/31	31.0 - 36.0	31	70
P20/36	36.0 - 41.0	36	75
P20/41	41.0 - 47.0	41	75
P20/47	47.0 - 54.0	47	85
P20/54*	54.0 - 61.0	54	85

*Non standard dies



Hydraulic Hose & Fittings

Looking for hydraulic hose and fittings to go with your new swaging machine? We stock large quantities of hydraulic hose and fittings for use across every industry including; 1 wire, 2 wire, 4 wire and 6 wire hose, and fittings available in mild or stainless steel.

Looking to start a mobile hose replacement business?

We have a recommended starting stock list for any new van, speak to our sales team to discuss your specific needs.

30+ Years in the Hydraulic Industry





