

4SP HYDRAULIC HOSE

Global Flex Hydraulic Hose

All high pressure hydraulic applications where a durable, flexible hose is required.





SPECIFICATIONS

HOSE			INSIDE Ø		OUTSIDE Ø	WORKING PRESSURE		BURST PRESSURE	BEND RADIUS	WEIGHT
part number	dash size	DN	inch	mm	mm	bar	psi	bar	mm	kg/m
GF4SP08	-8	12	1/2	12.7	23.8	415	6020	1660	230	0.89
GF4SP12	-12	19	3/4	19.0	31.4	350	5075	1400	300	1.50
GF4SP16	-16	25	1	25.4	38.5	280	4060	1120	340	2.00

Tube

Oil resistant synthetic rubber

Reinforcement

Four high tensile steel wire braids

Cove

Oil and weather resistant synthetic rubber

Temperature

-40°C to +155°C

Standards

DIN EN 856 4SP



Global Flex Swaging Machines

Looking to make your own hydraulic hoses? Did you know Hydraulic Megastore offers a wide range of Global Flex swaging machines available in hand pump, air pump, 12V, single and three-phase.

We also offer 12V cutting machines for vehicle hose replacement and single phase and three-phase cutting machines for workshop locations. Contact our sales team today for more information!

30+ Years in the Hydraulic Industry







